

2026 – Front Wheel Drive Rules

Note: JR. FWD will follow the same rules but must be between 12 & 15 years old.

Cars:

4 Cylinder Front Wheel Drive cars only.

Weight:

2200lbs with driver.

No per lap burn off.

Engine:

Must be stock for make. (I.E. Chevy to Chevy, Ford to Ford, Honda to Honda, etc.) No interchanging makes.

No turbo or rotary engines allowed.

Fuel injection only.

Aftermarket air filters allowed. Tube from throttle body to air filter can be aftermarket, plastic, steel or rubber. Must be in the engine compartment.

No aftermarket intakes, head or blocks.

ECM can be programmed or upgraded.

Transmission:

Stock automatic or stock manual transmission.

May be locked or welded.

Drive Line:

Front wheel drive only.

Rear axle must be stock for make and model.

Right Rear may run safety hub.

Suspension:

No screw jacks

No adjustable suspension components

Shocks & Springs must be in stock location

No adjustable or aluminum shocks.

Body:

Two door or four door

All glass, interior (plastic, carpet, molding, fabric) must be removed.
Aftermarket front and rear bumper covers allowed.

Roll Cage:

Minimum of a six-point cage, minimum of 1.50" x .095" diameter steel, 3 door bars minimum on drivers and passenger side with connecting bars between door bars. Main hoop must have diagonal or X bar behind driver. Must have 1 diagonal bar in halo of cage. Cage must be welded to frame or welded to 1/8" steel plates that are welded to the uni body. Minimum of 3 window bars in front of driver 3/8" or larger in diameter.

Track officials reserve the right to deem any cage unsafe for competition and must be corrected before allowed to compete.

Driver's Compartment:

Racing seat required and must be properly mounted.
5-point racing harness required, must be within date and properly mounted.
Fire extinguisher with in driver's reach mandatory.
Battery disconnect switch must be in reach of driver and safety crew.
Battery must be enclosed if located in driver's compartment.

Tires & Wheels:

Highway DOT tires only. **NO RACING TIRES.**
Racing wheels allowed. 8-inch MAX.
Bead Locks allowed.

Fuel:

Gas or Racing Fuel ONLY.
No Alcohol or Methanol.
Fuel cells or tanks must be securely fastened and sealed from driver's compartment.

Brakes:

Must be stock for make and model.
No brake adjusters.

Safety:

SA2015 or newer helmet with full shield required. No motorcycle helmets allowed.
SFI rated racing suit required. Top and Bottom. No Jeans, No work pants.
SFI rated racing gloves strongly recommended.
SFI rated racing shoes strongly recommended.
SFI rated head and neck restraint strongly recommended.
Raceiver/Nitrobee One-Way communication required. Only one receiver permitted in car. **No two-way radios, cell phones, or rear-view mirrors permitted.**

--- IF ITS NOT IN THE RULES DO NOT DO IT---

RULE BOOK DISCLAIMER

The rules and/or regulations set forth herein are designed to provide for the orderly conduct of racing events and to establish minimum acceptable requirements for such events. These rules shall govern the condition of all events, and by participating in these events, all participants are deemed to have complied with these rules. No express or implied warranty of safety shall result from publications of or compliance with these rules and/or regulations. They are intended as a guide for the conduct of the sport and are in no way a guarantee against injury or death to a participant, spectator or official. The race director shall be empowered to permit minor deviation from any of the specifications herein or impose any further restrictions that in his opinion do not alter the minimum acceptable requirements. No expressed or implied warranty of safety shall result from such alteration of specifications. Any interpretation or deviation of these rules is left to the discretion of the officials. Their decision is FINAL.